



**FOR INSTITUTIONAL, COMMERCIAL  
AND INDUSTRIAL USE**

**DIRECTIONS**

First remove all material possible with a scraper or dull knife. Then hold snorkel tube about 2 inches from substance and spray with a 5 to 10 second blast. While material is hard and brittle, scrape rapidly with a dull knife or scraper; repeat as necessary.

**Cautions:** Do not swallow. Avoid eye and prolonged skin contact. Avoid breathing vapors. Use in well ventilated area. Do not smoke while using. Keep away from heat sources, sparks, flames and other sources of ignition. Do not puncture or incinerate (burn) container, even when empty. Do not expose

to heat or store above 120°F (49°C) as containers may burst. Do not place can on hot surfaces or in direct sunlight. Intentional inhalation abuse (concentrating and inhaling vapors) may be harmful or fatal. **FIRST AID: INGESTION:** Do not induce vomiting. Call physician or poison control center immediately. **EYE CONTACT:** Flush with water for at least 15 minutes. Get immediate medical attention. **SKIN CONTACT:** Wash with soap and water. If irritation develops, get medical attention. **INHALATION:** Move to fresh air. Get medical attention if irritation or other symptoms develop and persist. **KEEP OUT OF REACH OF CHILDREN.** **CONTAINS (CAS No.):** Ethanol (64-17-5) and Liquefied Petroleum Gas (68476-86-8).

**HMIS® INDEX:**

0=MINIMAL 1=SLIGHT

2=MODERATE 3=SERIOUS 4=SEVERE

HEALTH	1
FLAMMABILITY	4
REACTIVITY	0
PERSONAL PROTECTION	X

\* = CHRONIC

See M.S.D.S. for complete safety information.  
24 HOUR MEDICAL EMERGENCY: 1-866-836-8855  
**CONTAINS NO OZONE DEPLETING CHEMICALS!**

**Item # CS0170**

Distributed by:



Las Vegas, NV 89118 (702) 876-3990

[www.bradyindustries.com](http://www.bradyindustries.com)

**BRADY**

# Gum Remover

## Removedor de Chicle



**CAN ALSO BE USED EFFECTIVELY FOR  
REMOVING CANDLE WAX, PUTTY AND  
OTHER GUMMY SUBSTANCES**

**CARPET CARE**

**DANGER: EXTREMELY FLAMMABLE  
EYE IRRITANT  
CONTENTS UNDER PRESSURE  
Read carefully other cautions on back panel.  
NET WT. 6.5 OZ. (184 g)**