



Use to remove wax build-up from baseboards, floors and ceramic wall tiles.

DIRECTIONS

1. Shake well before using.
2. Check the product on a small inconspicuous area of the surface to be sprayed to make sure there is no attack. Do not spray on painted or varnished surfaces. Wipe off any overspray immediately.
3. Turn can UPSIDE DOWN and hold 6-10 inches from baseboard or surface to be sprayed. A thin even coating should cover the wax.
4. Wait 3 to 5 minutes, longer in case of substantial build-up. Wet scrub the surface with an abrasive pad or scrub brush. Repeat until all wax is removed.
5. Rinse surface with clean water and allow area to dry thoroughly before re-polishing.

CAUTIONS: Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation. Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Prolonged inhalation may be harmful. Do not get this material in contact with eyes or skin. Keep away from heat, sparks and flames. Do not puncture, incinerate or crush. Do not expose to heat or store at temperatures above 120°F (49°C) as container may burst. Avoid prolonged exposure to sunlight. Use with adequate ventilation. **FIRST AID: EYES:** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately. **SKIN:** Immediately flush skin with plenty of water. Get medical attention immediately. **INHALATION:** Move to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Get medical attention immediately. **INGESTION:** Immediately contact a poison control center. Have victim rinse mouth thoroughly with

water. Do not induce vomiting without advice from poison control center. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. KEEP OUT OF REACH OF CHILDREN.

CONTAINS (CAS No.): Water (7732-18-5), 2-Butoxyethanol (111-76-2), Alkyl Phenol Ethoxylate Phosphate Ester (68412-53-3), and Liquefied Petroleum Gas (68476-86-8).

Precauciones: El contacto prolongado o repetido puede secar la piel y resultar en una irritación de la piel. El abuso no deseado o intencional por concentrar e inhalar el producto puede ser dañino o fatal. La inhalación prolongada puede ser dañina. Este material no debe tener el contacto con los ojos o la piel. Manténgase alejado del calor, chispas, y llamas. No perforo, incinere ni aplaste el envase. No exponga al calor ni almacene en temperaturas superiores a 120°F (49°C) ya que el envase puede explotar. Evite la exposición prolongada a al luz solar. Use con la ventilación adecuada. **PRIMEROS AUXILIOS: OJOS:** Lave inmediatamente con abundante agua por lo menos 15 minutos. Quite las lentillas, si están presentes y es fácil para hacer. Siga enjuagando los ojos. Obtenga atención médica inmediatamente. **PIEL:** Lave inmediatamente con una cantidad suficiente de agua. Obtenga atención médica inmediatamente. **INHALACIÓN:** Salga al aire fresco. Oxígeno o respiración artificial si necesario. No use el método de boca a boca si la víctima ha inhalado la sustancia. Obtenga atención médica inmediatamente. **INGESTIÓN:** Láme inmediatamente el Centro de Control de Envenenamientos. La víctima debe lavar la boca bien con agua. No induzca el vómito sin los consejos del Centro de Control de Envenenamientos. Si ocurre el vómito naturalmente, haga que la víctima se incline para reducir el riesgo de aspiración. MANTÉNGASE ALEJADO DEL ALCANCE DE LOS NIÑOS.

HMIS® INDEX:

0=MINIMAL 1=SLIGHT
2=MODERATE 3=SERIOUS 4=SEVERE

HEALTH	1*
FLAMMABILITY	2
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X

See M.S.D.S. for complete safety information.

24 HOUR MEDICAL EMERGENCY/24 HORAS EMERGENCIAS MÉDICAS:

1-866-836-8855

CONTAINS NO OZONE DEPLETING CHEMICALS!

Item # CW0050



Las Vegas, NV 89118 (702) 876-3990
www.bradyindustries.com

BRADY

Build Off

Baseboard Wax Stripper

Producto para Quitarles el Acabado de Cera en Rodapiés



REMOVES HEAVY BUILD-UP IN HARD TO REACH AREAS...

Floors, Baseboards,
Ceramic Wall Tile

Clinging Foam Adheres to Surfaces
Easy Rinsing

USE IN UPSIDE DOWN POSITION ONLY

FLOOR CARE

CAUTION
MAY CAUSE EYE IRRITATION.
CONTENTS UNDER PRESSURE.
Read carefully other cautions on back panel.

Net Wt. 19 oz. (1 lb. 3 oz.) 539 g